

Equations $p(h,s)$ for Water and Steam

H.-J. Kretzschmar, I. Stöcker, and K. Knobloch
Department of Technical Thermodynamics
University of Applied Sciences of Zittau and Görlitz
D-02754 Zittau, Germany

J. Trübenbach, T. Willkommen, and A. Dittmann
Department of Technical Thermodynamics
Technical University of Dresden
D-01062 Dresden, Germany

The new Industrial Formulation IAPWS-IF97 for the thermodynamic properties of water and steam was adopted since September 1997. Besides fundamental equations, the IAPWS-IF97 contains equations for the most often used backward functions, $T(p,h)$ and $T(p,s)$, valid in the liquid and the vapor regions.

In addition to these, equations for the backward function $p(h,s)$, which is also used in process modeling, will be presented. . The range of validity of these equations corresponds to that of the backward equations of the IAPWS-IF97. Their numerical consistency with the basic equations, $s(p,T)$ and $h(p,T)$ of the IAPWS-IF97 is sufficient for application in heat cycle and steam turbine calculations.

With pressure $p(h,s)$, the temperature can be calculated using the IAPWS-IF97 backward equation $T(p,h)$. Because the numerical consistency of the temperature obtained in this way is also sufficient for thermodynamic process modeling, the otherwise inevitable iterations of p and T from the IAPWS-IF97 equations $s(p,T)$ and $h(p,T)$ can be avoided.

The basis for developing the equations $p(h,s)$ is a special approximation algorithm of Trübenbach and Willkommen. It is based on the structural optimization method of Wagner. The modification takes into account the computing time to run the equation while it is being developed and contains optimization of the nonlinear parameters.